

# XO OR OX SIZE CHART AND COLONIAL LITE CONFIGURATIONS

## SERIES HR201 & HR610

COMMODITY

WINDOW WIDTH	26½	37	53½	74				
MASONRY OPENING	27¼	37¾	53⅞	74¼				
WOOD FRAME OPENING	25¼	36¼	52⅝	73¼				
ALUMINUM FRAME OPENING	25⅝	36⅞	52¼	73⅞				
26	26	25¼	25⅛	H32	22	32	D22	
38¾	38¾	37⅝	37½	H33	23	33	D23	
50⅝	50⅝	49⅞	49¾	H34	24	34	D24	
63	63	62¼	62⅛	H35	25	35	D25	
72	72	71¼	71⅛	H3M	2M	3M		HR201 ONLY

MODULAR

WINDOW WIDTH	24	36	48	54	60	66	72	74			
MASONRY OPENING	24¾	36¾	48¾	54¾	60¾	66¾	72¾	74¾			
WOOD FRAME OPENING	23¼	35¼	47¼	53¼	59¼	65¼	71¼	73¼			
ALUMINUM FRAME OPENING	23⅞	35⅞	47⅞	53⅞	59⅞	65⅞	71⅞	73⅞			
24	24	23¼	23⅛	2020	3020	4020	4620	5020	5620	6020	6220
36	36	35¼	35⅛	2030	3030	4030	4630	5030	5630	6030	6230
48	48	47¼	47⅛	2040	3040	4040	4640	5040	5640	6040	6240
54	54	53¼	53⅛	2046	3046	4046	4646	5046	5646	6046	6246
60	60	59¼	59⅛	2050	3050	4050	4650	5050	5650	6050	6250
66	66	65¼	65⅛	2056	3056	4056	4656	5056	5656	6056	6256
72	72	71¼	71⅛	2060	3060	4060	4660	5060	5660	6060	6260

HR201 ONLY

### HR201 EGRESS FORMULA (INCHES)

NOTE: Check your local building code for Egress requirements. Not all window sizes are manufacturable. Check product catalog to ensure PGT offers the desired size. PGT reserves the right to change material design and/or construction without notice or liability.

XO – OX	[(Window width / 2 – 3.5)	x (Window height – 4.625)] / 144	= Overall Clear Opening (ft²)
XOX (¼, ½, ¾)	[(Window width / 4 – 2.312)	x (Window height – 4.625)] / 144	= Overall Clear Opening (ft²)
XOX (⅓, ⅓, ⅓)	[(Window width / 3 – 5.984)	x (Window height – 4.625)] / 144	= Overall Clear Opening (ft²)

WINDOW HEIGHT  
MASONRY OPENING  
WOOD FRAME OPENING  
ALUMINUM FRAME OPENING


# XOX SIZE CHART AND COLONIAL LITE CONFIGURATIONS

## SERIES HR201 & HR610


COMMODITY

WINDOW WIDTH	53 1/8	74	106 3/8	111	120
MASONRY OPENING	53 7/8	74 3/4	107 1/8	111 3/4	120 3/4
WOOD FRAME OPENING	52 3/8	73 1/4	105 5/8	110 1/4	119 1/4
ALUMINUM FRAME OPENING	52 1/4	73 1/8	105 1/2	110 1/8	119 1/8

26 26 25 1/4 25 1/8



38 3/8 38 3/8 37 3/8 37 1/2



50 5/8 50 5/8 50 7/8 49 3/4




63 63 62 1/4 62 1/8



MODULAR

WINDOW WIDTH	48	60	72	74	84	96	108	120
MASONRY OPENING	48 3/4	60 3/4	72 3/4	74 3/4	84 3/4	96 3/4	108 3/4	120 3/4
WOOD FRAME OPENING	47 1/4	59 1/4	71 1/4	73 1/4	83 1/4	95 1/4	107 1/4	119 1/4
ALUMINUM FRAME OPENING	47 1/8	59 1/8	71 1/8	73 1/8	83 1/8	95 1/8	107 1/8	119 1/8

24 24 23 1/4 23 1/8




36 36 35 1/4 35 1/8




48 48 47 1/4 47 1/8



54 54 53 1/4 53 1/8



60 60 59 1/4 59 1/8



WINDOW HEIGHT  
MASONRY OPENING  
WOOD FRAME OPENING  
ALUMINUM FRAME OPENING

Note: Openings calculated using 1/8" shim space (maximum 1/4" allowed) 1x bucks and precast sill. If using poured sills, add 3/4". Framing dimensions are calculated with drywall butted.

### HR610 EGRESS FORMULA (INCHES)

NOTE: Check your local building code for Egress requirements. Not all window sizes are manufacturable. Check product catalog to ensure PGT offers the desired size. PGT reserves the right to change material design and/or construction without notice or liability.

XO – OX                    [(Window width / 2 – 4.5)                    x (Window height – 5.75)] / 144                    = Overall Clear Opening (ft<sup>2</sup>)  
 XOX ( 1/4,1/2,1/4 )                    [(Window width / 4 – 3.375)                    x (Window height – 5.75)] / 144                    = Overall Clear Opening (ft<sup>2</sup>)  
 XOX ( 1/3,1/3,1/3 )                    [(Window width / 3 – 4.625)                    x (Window height – 5.75)] / 144                    = Overall Clear Opening (ft<sup>2</sup>)